

Galexio

Global Ticketing Solutions



- Modular and upgradable
- Functional and compact
- Cost-effective operation
- Accessible to people with reduced mobility



Technical specifications - Galexio 500 and Galexio 600

<p>General design</p>	<p>Casing: highly secure access and multipoint locking system, anti-corrosion, anti-graffiti, anti-UV treatment</p> <p>Operational: from -20 °C to +50 °C at 90% HR Heating/ventilation device to regulate temperature</p> <p>Interior or exterior installation, with or without shelter</p> <p><u>Galexio 500</u> Dimensions (HxWxD): 1680 x 560 x 395 mm. Optional cap for extra information area Total weight: 190 kg to 270 kg, depending on configuration</p> <p><u>Galexio 600</u> Dimensions (HxWxD): 1800 x 650 x 420 mm Total weight: 215 kg approx, depending on internal configuration</p>
<p>Electric power supply</p>	<p>Safety: EN 60-950 and CE mark Main protection: 16 A / 30 mA differential and 10A heating/ventilation circuit</p> <p>Back-up sector supply: Two 12 V - 3 Ah batteries Completion of transactions in the event of a power cut</p> <p>Consumption: 230 W max with heating off, 2000 W max with heating on, depending on option</p>
<p>Accessibility for people with reduced mobility</p>	<p>Compliant with the following standards: CEMT (EU), COLIAC (France), DDA (UK), ADA (USA) and STI interoperability directives</p>
<p>User interface</p>	<p>User interface integrated in recess</p> <p>Single collection tray for tickets and coins</p> <p>Options: multilingual, audio assistance by dynamic voice synthesis, on screen ad space</p> <p><u>Galexio 500</u> Colour LCD screen of up to 12 inches, min resolution 800x600, min brightness 400 Cd/m² 12-inch touch screen or selection knob, with 10.4-inch screen</p> <p><u>Galexio 600</u> Colour LCD screen of up to 15 inches, min resolution 1024x768, min brightness 400 Cd/m² 15-inch touch screen or selection knob, with 12-inch screen</p>
<p>Methods of payment</p>	<p>Coin payment: up to 13 types of coin accepted</p> <p>Bank payment approved by MPA 5.2, EMV 2000 (EMVCo Level 1 and 2), AFAS, PCI PED and Visa PABP and compliant with SEPA specifications</p> <p><u>Galexio 600</u> Recycling for 5 types of coin with 50 coins per recycler on average Storage option: up to 3 extra storage spaces with the capacity of about 500 coins each, according to types chosen</p>
<p>Tickets and receipts</p>	<p>Printing and distribution of thermal tickets, with or without magnetic strip</p> <p>Encoding: TFC0 & TFC1 formats compliant with standard ISO/CEI 15457-1, roll or sheet storage, up to 4 entries</p> <p>Printing, distribution, recharging of contactless tickets (CTS512, SRT512, Mifare UL, SRX4K, CTM512...)</p> <p>Recharging of type A, B et B' cards compliant with standard ISO 14443</p> <p>Standards met: Intercode I, II and 2008, Intertic rev2, ITSO</p>
<p>CPU</p>	<p>Industrial rackable PC</p> <p>Embedded Windows XPE operating system</p> <p>Offset connector integrating monitoring and communication functions</p> <p>External communication via Ethernet, ADSL, Wi-Fi, GPRS/3G, standard protocol FTP, TCP/IP</p>
<p>Ecological design</p>	<p>All models in the Galexio range comply with the directives RoHS 2002/95/CE and DEEE 2002/96/CE and are more than 95% recyclable</p>